

Technical Data

153M



Stamped

Floor Registers 3-Way Deflection

		Face Jet Velocity	300	400	500	600	700	800	900	1000
		Static Pressure Loss	0.006	0.010	0.016	0.023	0.031	0.042	0.052	0.064
Size										
Ak										
4 x 10	CFM	48	64	80	96	112	128	144	160	
	L Throw	3.6	4.2	4.7	5.5	6.2	6.4	6.5	6.7	
	0.160 S Throw	1.8	2.2	2.7	3.9	5.1	5.5	5.9	6.5	
4 x 12	CFM	57	75	95	114	133	152	171	191	
	L Throw	3.9	4.3	4.9	5.7	6.7	6.9	7.1	7.3	
	0.190 S Throw	1.8	2.4	3	4.3	5.5	5.9	6.3	7	
4 x 14	CFM	68	90	113	136	158	181	203	225	
	L Throw	4.2	4.9	5.6	6.5	7.4	7.7	7.8	8	
	0.226 S Throw	2	2.6	3.2	4.6	6	6.4	6.9	7.6	
6 x 10	CFM	72	95	119	143	166	191	214	238	
	L Throw	4.2	4.9	5.6	6.3	7.2	7.4	7.6	8.2	
	0.238 S Throw	2	2.6	3.2	4.7	6.1	6.6	7	7.5	
6 x 12	CFM	86	114	142	171	200	228	257	285	
	L Throw	4.8	5.4	6	6.9	7.8	8.1	8.5	8.7	
	0.285 S Throw	2.1	2.8	3.5	5.1	6.7	7.1	7.5	8.3	
6 x 14	CFM	101	135	168	202	235	268	301	336	
	L Throw	5.1	6.5	6.8	7.6	8.7	9	9.1	9.5	
	0.336 S Throw	2.3	2.8	3.7	5.5	7.1	7.6	8.2	9	